



CLASSIC 290 PC Stand

Start-up Electric Airless Paint Sprayer



PROFESSIONAL ADVANTAGES

- Ideal for renovation or new construction family house painting
- Finish every job, every day thanks to ProConnect™ fast pump replacement system
- Compact, lightweight and easy to use – supports a 0.021" tip

MATERIALS

Lacquers - Acrylics - Primers - Enamels - Varnishes – Emulsions

Painter - Fine Finish & Professional Airless Applications

CLASSIC 290 PC Stand



CLASSIC 290 PC Stand

Start-up Electric Airless Paint Sprayer

Endurance™ Pump Design

- Graco's proven airless pump design
- Delivers long life and reliable performance
- Quick access for easy cleaning or repair



Lightweight Design

- Offset handle with rubber comfort grip is positioned to kick sprayer away from leg for comfortable carrying



Easy Out™ Pump Filter

- Large inside-out filtering area reduces tip clogs and ensures a quality finish



Variable Pressure Control

- Position indicator allows repeatable setting while spraying light-to heavier materials



Swivel Inlet Suction Hose

- All aluminium construction is durable, lightweight and rust-proof
- No-tools removal of hose for cleaning or accessing inlet ball
- Easily swivels to reach paint buckets or cans

Chrome Plated, Welded Steel Frame

- Thick chrome over steel to withstand rugged environments



CLASSIC 290 PC Stand – Advanced Features



Exchange your pump easily **YOURSELF** in 3 steps in case any damage appears.

No more time wasted or money lost to labour charges on pump repairs.

Fast Pump Replacement

- 1-minute job site replacement
- Keeps you spraying instead of waiting for service
- No pins or parts to lose!



Loosen the clamping nut



Open door and remove pump



Remove hose and suction tube

TIP!

With a spare pump ready, you'll always be able to finish your job!



TIP!
Configure your sprayer to a customized Airless Enamel sprayer!

Add a 5 liter hopper and a shorter 7.5 m x 3/16" hose with a FFA tip. This compact configuration offers extreme gun and hose handling flexibility and limits material inside the unit to a minimum. COMPLETE WITH pre-atomisation FFA tips for extreme fine finish quality.

CLASSIC 290 PC Stand

SPECIFICATIONS

CLASSIC 290 PC Stand

Part Number:	
for EURO version 230 V	17C344
110 V	-
Max. Working Pressure - bar (PSI)	230 (3300)
Max. Fluid Flow - l/min.	1.8 (0.47)
Max. Tip Size - 1 gun	0.021"
Weight - kg (lbs)	17 (37.5)
Motor Rating - kW (HP)	0.46 (0.625)
Motor Type	DC/Brush

Unit ships complete* with: FTX™-E gun (288438) including RAC X (PAA517) tip and guard, BlueMax™ II hose 1/4" x 15 m (240794), set-up tools.

* Unit can be extended with material filter (249056), pressure gauge (115523) and 24W090 ProGuard+ for optimal setting, control and power protection.

ACCESSORIES

Guns

288438 FTX™-E Gun, RAC X™ 517 tip, RAC X guard and 2 filters

BlueMax™ II Hoses & Whips

238358 3/16" x 0.9 m
214698 3/16" x 7.5 m
240794 1/4" x 15 m
223771 1/4" x 30 m

Easy Out™ Gun Filters

287032 60 Mesh x 1
287033 100 Mesh x 1

Easy Out Pump Filters - CLASSIC Manifold Filters

243080 60 Mesh, black
243081 100 Mesh, blue
243226 200 Mesh, red

ProConnect Pump Lower

17C489 Blister Pack

ProGuard™+

24W090 230V, CEE 7/7, shuko

Pro Tip Extensions - RAC X Guard

287019 (25 cm) | 287021 (50 cm)
287020 (40 cm) | 287022 (75 cm)

JetRoller™ with Inline™ Gun

24V490 Roller 18 cm
24V491 Roller 25 cm

Hopper

288526 Hopper (5 liter)

Roller Kits

245397 Roller Kit (Int.) 50 cm
244281 Telescopic Roller (45-90 cm)

Tips & Guards

FFAXXX Green RAC X
Fine Finish Tip
PAAXXX Blue RAC X Professional
Airless Tip
246215 Guard RAC X 7/8"
246437 Guard RAC X 11/16"

Liquids

206994 TSL™ 0.25 l
253574 Pump Armor™ 1 l

Find this unit at:



Watch our **application videos** at: <http://www.contractorclub.com>